

InnoVet Classic



Specifications

- ~ mA stations: 100S, 300L
- ~ kVp range: 40 - 125, 64 selections
- ~ Timer range: 1/120th - 1 second, 13 selections
- ~ Built-in tube protection
- ~ mAs range: 1.0 - 300 mAs
- ~ Digital kVp readout
- ~ Tilt out control panel
- ~ Solid state adjustable, audible exposure signal
- ~ SCR contactor
- ~ UL classified



Control panel



Digital kVp readout

Table / Tubestand

- ~ Enclosed, integrated radiographic table
- ~ Table top: 56" x 24"
- ~ Welded base construction
- ~ Grid cabinet with Simplex™ cassette tray
- ~ Grid: 8:1 ratio, 103 LPI
- ~ Grid cabinet / tablestand interlock
- ~ Angulation dial and operator handgrips
- ~ Foot switch with 20 ft. cord
- ~ UL classified

X-Ray Tube


- ~ 1.0 - 2.0 mm F.S.
- ~ 140,000 H.U. with 90 degree horns

Cables

- ~ 10 ft. high voltage cables with federal terminations

Collimator

- ~ Manual collimator with light field
- ~ Swivel mount
- ~ Field light "on" time - adjustable 30 - 120 seconds
- ~ Long life "soft-start" bulb circuits
- ~ Meets federal standards for radiation leakage protection



Simplex
Cassette Tray

